



		Tires		Clutch settings		Front shocks		Engine								
Date/Track	8/11/2013 Asia RC New Taipei City Cup	Front shore	left ZAC 32° / right ZAC 32°	Shoe / Bell	Black / Al. Bell	Piston	1.3x1	Type	O.S Speed 21XZ-R							
Driver	Takaaki Shimo	Rear shore	left ZAC 35° / right ZAC 35°	Bell clearance (mm)	0.6	Oil	600	Plug/Fuel	Plug RP7 / Fuel COSMO							
Temp. °C.	air / track	Front φ	left 69 / right 69	Spring/adj. Nut(mm)	H2706 / 0	Spring	Gray	Pipe/Manifold	Pipe T-2080 / Manifold							
Track layout/traction	technical <input type="radio"/> low <input type="radio"/> mixed <input type="radio"/> medium <input type="radio"/> fast <input type="radio"/> high <input type="radio"/>	Rear φ	left 75 / right 75	Bell axial play (mm)	0.2	Rear shocks		Gear ratio chart								
		Body		Gearing		Piston	1.1x2			1st	2nd					
		Type	Protoform R15B	1st gear	16 / 50	Oil	600			48	49	50	45	46	47	
		Wing position (mm)		2nd gear	20 / 46	Spring	Gray			1st	16	7,2	7,35	7,5		
										19	6,776	6,918	7,059			
										2nd	20			5,684	5,811	5,937
										21			5,4	5,52	5,64	
												5,143	5,257	5,371		

