



		Tires		Clutch settings		Front shocks		Engine							
Date/Track	01.07.13	Front shore	left 32 / right 32	Shoe / Bell	kit / kit	Piston	1 standard	Type							
Driver	Robert Pietsch	Rear shore	left 35 / right 35	Bell clearance (mm)	0,6	Oil	500	Plug/Fuel	Plug	Fuel					
Temp. °C.	air / track	Front φ	left 68 / right 68	Spring/adj. Nut(mm)	kit / 0,1-0,2	Spring	grey	Pipe/Manifold	Pipe	Manifold					
		Rear φ	left 75 / right 75	Bell axial play (mm)	0,1-0,2	Rear shocks		Gear ratio chart							
Track layout/traction	technical <input type="radio"/> low <input type="radio"/>	Body		Gearing		Piston	2 standard	1st		2nd					
	mixed <input checked="" type="radio"/> medium <input checked="" type="radio"/>	Type	PFR18	1st gear	16 / 50	Oil	600	1st	16	48	49	50	45	46	47
	fast <input type="radio"/> high <input type="radio"/>	Wing position (mm)	8	2n gear	20 / 45	Spring	grey	1st	17	7,2	7,35	7,5			
								2nd	19	6,776	6,918	7,059	5,684	5,811	5,937
									20				5,4	5,52	5,64
									21				5,143	5,257	5,371

