



		Tires		Clutch settings		Front shocks		Engine			
Date/Track	19.10.14	Front shore	left 32 / right 32	Shoe / Bell	Standard	Piston	1 standard	Type	Picco torque		
Driver	ENS RD4 Fiorano	Rear shore	left 35 / right 35	Bell clearance (mm)	0,6	Oil	600	Plug/Fuel	Plug P7TC / Fuel Maxima		
Temp. °C.	air / track	Front φ	left 69 / right 69	Spring/adj. Nut(mm)	kit / 0,5mm	Spring	silver (T2505)	Pipe/Manifold	Pipe 2120 / Manifold short		
		Rear φ	left 76 / right 76	Bell axial play (mm)	0,1-0,2		Rear shocks	Gear ratio chart			
Track layout/traction	technical <input type="radio"/> low <input type="radio"/>	Body			Gearing		Piston	2 standard		1st 48 49 50 2nd 45 46 47	
	mixed <input checked="" type="radio"/> medium <input checked="" type="radio"/>	Type	PFR18		1st gear	16 / 50	Oil	700		1st 16 17 19 2nd 20 21	7,2 7,35 7,5 6,776 6,918 7,059 5,684 5,811 5,937 5,4 5,52 5,64 5,143 5,257 5,371
	fast <input type="radio"/> high <input type="radio"/>	Wing position (mm)	8		2n gear	20 / 46	Spring	silver (T2506)			

