



		Tires		Clutch settings		Front shocks		Engine									
Date/Track	Keitune 26.5.13	Front shore	left 32 / right 32	Shoe / Bell	black / optional bell alu	Piston	1 standard	Type									
Driver	Robert Pietsch	Rear shore	left 35 / right 35	Bell clearance (mm)	0,6	Oil	500	Plug/Fuel	Plug	Fuel							
Temp. °C.	air / track	Front φ	left 68 / right 68	Spring/adj. Nut(mm)	kit / 0,3mm	Spring	grey	Pipe/Manifold	Pipe	Manifold							
		Rear φ	left 75 / right 75	Bell axial play (mm)	0,1-0,2		Rear shocks	Gear ratio chart									
Track layout/traction	technical <input type="radio"/> low <input type="radio"/>	Body		Gearing		Piston	2 standard			1st	48	49	50	2nd	45	46	47
	mixed <input checked="" type="radio"/> medium <input checked="" type="radio"/>	Type	PFL128	1st gear	16 / 50	Oil	600	1st	16	7,2	7,35	7,5					
	fast <input type="radio"/> high <input type="radio"/>	Wing position (mm)	8	2n gear	20 / 46	Spring	grey	2nd	19	6,776	6,918	7,059			5,684	5,811	5,937
									20						5,4	5,52	5,64
									21					5,143	5,257	5,371	

