

DRIVER	Takaaki Shimo	
DATE	2016/10/16	
TRACK	Hokusei Circuit, Japan Nats	

TRACTION		
LOW <input type="checkbox"/>	MEDIUM <input checked="" type="checkbox"/>	HIGH <input type="checkbox"/>

LAYOUT		
SLOW <input type="checkbox"/>	MIXED <input checked="" type="checkbox"/>	FAST <input type="checkbox"/>

ENGINE		
TYPE	O.S. Shimo Edition	
GLOW PLUG/FUEL PIPE/MANIFOLD	RP7	Nitrox
	O.S - T - 2080	O.S

CLUTCH SETTINGS		
SHOE#/BELL#	STD	STD
CLEARANCE(mm) / AXIALPLAY(mm)	0.7	0.2
SPRING#/TENSION(mm)	STD	0.3

TYRES				
CONTROLLED <input checked="" type="checkbox"/>				
FRONT		BRAND	REAR	
LEFT	RIGHT	ZAC	LEFT	RIGHT
30°	30°	SHORE	35°	35°
69	69	DIAMETER START	76	76
		DIAMETER 5min		

SHOCK ABSORBERS			
FRONT		REAR	
PISTON	1.3x1	PISTON	1.1x2
OIL	600	OIL	600
SPRING	Serpent Purple	SPRING	Serpent Red

ANTI ROLL BAR FRONT			
2,2 <input type="checkbox"/>	2,3 <input type="checkbox"/>	2,4 <input checked="" type="checkbox"/>	2,5 <input type="checkbox"/>
ANTI ROLL BAR REAR			
2,8 <input type="checkbox"/>	2,9 <input checked="" type="checkbox"/>	3,0 <input type="checkbox"/>	

SERVO SAVER POSITION			
FORWARD <input checked="" type="checkbox"/>	REARWARD <input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

PINION 1st	
15T <input checked="" type="checkbox"/>	16T <input type="checkbox"/>
PINION 2nd	
19T <input type="checkbox"/>	20T <input checked="" type="checkbox"/>
SPUR 1st	
48T <input checked="" type="checkbox"/>	49T <input type="checkbox"/>
50T <input type="checkbox"/>	
SPUR 2nd	
45T <input type="checkbox"/>	46T <input type="checkbox"/>
47T <input checked="" type="checkbox"/>	

STEERING ROD POSITION

T2803 **1** SHIM(mm)

H2112 FORWARD REARWARD

SHOCK HOLE

UP CENTER DOWN

UPPER ARM POSITION

CAMBER **1.5** **1.5** LEFT RIGHT

YES DISK NO

1 SHIM UNDER H0180(mm)

8.5 RIDE HEIGHT (mm) **0** DOWNSTOP (mm)

252 TRACK WIDTH (mm)

SHOCK/UPPER ROD POSITION

H0466G POSITION SHIM(mm) **4**

CAMBER **3.0** **3.0** LEFT RIGHT

DISK YES NO

SHOCK POSITION H2115

INSIDE OUTSIDE

LOWER ARM POSITION

UP CENTER DOWN

9.5 RIDE HEIGHT (mm) **8** DOWNSTOP (mm)

263.5 TRACK WIDTH (mm)

FRONT TOE

LEFT **1.5** RIGHT **1.5**

OUT IN

RADIOPLATE FLEX

FIXED OPEN

H2415 MOUNTED ON:

position mm **8.5**

H2504 H2414

REAR TOE

LEFT **2.0** RIGHT **2.0**

IN -OUT

WEIGHT DISTRIBUTION

GR. **Full**

POSITION **Full**

YES NO

H2322A

AERO/SETTING

WING POSITION

BODY TYPE **PF R18**

BODY POSITION TO BUMPER **26**

NOTES:

2016 JMRCB 1/8 Racing Car Japan National Championship