

DRIVER	Takaaki Shimo	
DATE	2016/9/25	
TRACK	GLARC	

TRACTION		
LOW <input type="checkbox"/>	MEDIUM <input checked="" type="checkbox"/>	HIGH <input type="checkbox"/>

LAYOUT		
SLOW <input type="checkbox"/>	MIXED <input checked="" type="checkbox"/>	FAST <input type="checkbox"/>

ENGINE		
TYPE	O.S. Shimo Edition	
GLOW PLUG/FUEL PIPE/MANIFOLD	RP7	Flashpoint
	O.S	O.S

CLUTCH SETTINGS		
SHOE#/BELL#	STD	H2711
CLEARANCE(mm) / AXIALPLAY(mm)	0.7	0.2
SPRING#/TENSION(mm)	STD	0.2

TYRES				
CONTROLLED <input type="checkbox"/>				
FRONT		BRAND	REAR	
LEFT	RIGHT	Flashpoint	LEFT	RIGHT
32	32	SHORE	35	35
68	68	DIAMETER START	74	74
		DIAMETER 5min		

SHOCK ABSORBERS			
FRONT		REAR	
PISTON	1.3x1	PISTON	1.1x2
OIL	600	OIL	600
SPRING	White	SPRING	White

ANTI ROLL BAR FRONT			
2,2 <input type="checkbox"/>	2,3 <input checked="" type="checkbox"/>	2,4 <input type="checkbox"/>	2,5 <input type="checkbox"/>
ANTI ROLL BAR REAR			
2,8 <input type="checkbox"/>	2,9 <input checked="" type="checkbox"/>	3,0 <input type="checkbox"/>	

SERVO SAVER POSITION			
FORWARD <input type="checkbox"/>	<input checked="" type="checkbox"/>	REARWARD <input type="checkbox"/>	
<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

PINION 1st	
15T <input checked="" type="checkbox"/>	16T <input type="checkbox"/>
PINION 2nd	
19T <input type="checkbox"/>	20T <input checked="" type="checkbox"/>

SPUR 1st		
48T <input checked="" type="checkbox"/>	49T <input type="checkbox"/>	50T <input type="checkbox"/>
SPUR 2nd		
45T <input type="checkbox"/>	46T <input type="checkbox"/>	47T <input checked="" type="checkbox"/>

STEERING ROD POSITION

T2803 SHIM(mm) **1**

H2112 FORWARD REARWARD

SHOCK HOLE

UP CENTER DOWN

UPPER ARM POSITION

CAMBER **1.5** **1.5** LEFT RIGHT

YES DISK NO

1 SHIM UNDER H0180(mm)

8.5 RIDE HEIGHT (mm) **0** DOWNSTOP (mm)

254 TRACK WIDTH(mm)

SHOCK/UPPER ROD POSITION

H0466G POSITION SHIM(mm) **4**

CAMBER **3.0** **3.0** LEFT RIGHT

DISK YES NO

9.5 RIDE HEIGHT (mm) **8.0** DOWNSTOP (mm)

265 TRACK WIDTH (mm)

SHOCK POSITION H2115

INSIDE OUTSIDE

LOWER ARM POSITION

UP CENTER DOWN

FRONT TOE

LEFT **1.5** RIGHT **1.5**

OUT IN

RADIOPLATE FLEX

FIXED OPEN

H2415 MOUNTED ON:

position mm **9.5**

H2414 H2504

REAR TOE

LEFT **2.5** RIGHT **2.5**

IN -OUT

WEIGHT DISTRIBUTION

GR. **-**

POSITION **Full**

YES NO YES NO

H2322A

AERO/SETTING

WING POSITION

BODY TYPE **PF R18**

BODY POSITION TO BUMPER **26**

NOTES:

2016 KO Propo Grand Prix at Greater LA RC