

DATE	8/26/2017
DRIVER	Atsushi Hara
TRACK	Green Park Speedway

CARPET ASPHALT

TRACTION

LOW MEDIUM HIGH

LAYOUT

SLOW MIXED FAST

ELECTRIC'S

STEERING SERVO	TYPE Futaba	SETTINGS BLS571SV
ESC	TYPE Yokomo BL-PRO4	SETTINGS
ENGINE	TYPE Yokomo	SETTINGS M3 - 4.5T

TYRES/ADDITIVE	TYPE Ride REX 34S	TYPE MTG V3 Yellow
----------------	-----------------------------	------------------------------

FRONT FULL	<input checked="" type="checkbox"/>	REAR FULL	<input checked="" type="checkbox"/>
MIN.	5	MIN.	5

SHOCK ABSORBERS

FRONT REAR

PISTON	Kit	PISTON	Kit
OIL	#450	OIL	#450
SPRING	Xray 2.5-2.8	SPRING	Xray 2.6

ANTI ROLL BAR FRONT

1,2 1,3 1,4 1,5

ANTI ROLL BAR REAR

1,1 1,2 1,3 1,4

SERVO SAVER POSITION

FORWARD	<input type="checkbox"/>	REARWARD	<input checked="" type="checkbox"/>
---------	--------------------------	----------	-------------------------------------

PINION **26T** SPUR **116T**

DIFF SPOOL

HIGH	<input type="checkbox"/>	HIGH	<input type="checkbox"/>
LOW	<input checked="" type="checkbox"/>	LOW	<input checked="" type="checkbox"/>

DIFF OIL CST **#3,000 - 5,000 1.2g**

SHOCK POSITION LOWER ARM

PART# REAR Kit PART# FRONT Kit

HOLE POSITION BALL LINK	INSIDE <input type="checkbox"/>	HOLE POSITION BALL LINK	INSIDE <input type="checkbox"/>
	OUTSIDE <input checked="" type="checkbox"/>		OUTSIDE <input checked="" type="checkbox"/>

FLEX

ULTRAFLEX	<input checked="" type="checkbox"/>
TOPDECK	<input checked="" type="checkbox"/>
SCREW'S ASSEMBLED	<input checked="" type="checkbox"/>

CASTER POSITION

Lower arm angle A2107A-D needs caster re-adjustment! 0.5°=0.5mm shim A2110E!

UPPER ARM POSITION

SHOCK HOLE

ROD POSITION

SHIM(mm)

SHIM(mm)

CAMBER LEFT **+2** RIGHT **+2**

FF: A2105A/A2104 1pc. 2pcs.

FR: A2105B/A2104 1pc. 2pcs.

0° LOWER ARM ANGLE 0°

-0.5° -0.5° +0.5° +0.5° +0.5° +0.5° -0.5° -0.5°

KICK-UP/ANTI-DIVE

FR FF

ROLL CENTER/ TRACK WIDTH (LEFT SIDE VIEW)

5.3 (mm) 5.4 (mm)

RIDE HEIGHT DOWNSTOP

Kit Offset(mm)

CAMBER LINK POSITION

SHIM(mm)

INSIDE OUTSIDE

SHOCK HOLE

SHIM(mm)

CAMBER LEFT **+2.5** RIGHT **+2.5**

RF: A2106B/A2104 1pc. 2pcs.

RR: A2106A/A2104 1pc. 2pcs.

FINAL TOE IN **3**

BOTH CENTER = 3° TOE IN

+0.5° -0.5° -0.5° -0.5° +0.5° +0.5°

KICK-UP/ANTI-DIVE

RF RR

ROLL CENTER/TOE IN/ TRACK WIDTH (RIGHT SIDE VIEW)

5.6 (mm) 4.2 (mm)

RIDE HEIGHT DOWNSTOP

Kit Offset(mm)

A2404

ASSEMBLED SCREW'S

A2405

INSIDE SHIM(mm)

OUTSIDE

TOE OUT°

WHEELBASE WEIGHT g.

1 (mm) 10 0 (mm) 1

10 Kit 0

WEIGHT g. CHASSIS# WEIGHT g.

75.5 (mm)

BODY POSITION

STEERING SHAFT MOUNTED ON

SERVOPLATE

CHASSIS

STEERING STOPPER A2304/A2305/A2306

$\phi 5$ $\phi 5.5$ $\phi 6$ NO

WING TYPE **RC Mission**

PF LTC-R LW

BODY TYPE

8 OVERHANG(mm)

NOTES:

タイヤウォーマー: 5分

Tire warmer: 5 min.