



		Tires		Clutch settings		Front shocks		Engine			
Date/Track	01.07.13	Front shore	left 37 / right 37	Shoe	std.	Piston	std.	Type			
Driver	Robert Pietsch	Rear shore	left 40 / right 40	Bell clearance (mm)	0.5mm	Oil	350	Plug/Fuel	Plug	Fuel	
Temp. °C.	air / track	Front φ	left 62 / right 62	Spring	H0764	Spring	dark blue	Pipe/Manifold	Pipe	Manifold	
		Rear φ	left 64 / right 64	Bell axial play (mm)	0.1-0.2				Gear ratio chart		
Track layout/traction	technical <input type="radio"/> low <input type="radio"/>	Differential		Gearing		Piston	std.	Spur Pinion		1st 52 53 54	2nd 47 48 49
	mixed <input checked="" type="radio"/> medium <input checked="" type="radio"/>	Front diff. oil cst.	solid		1st gear	14 / 52	Oil	350	1st 14 15 19 20 21	7,614 7,761 7,907	5,071 5,179 5,278
	fast <input type="radio"/> high <input type="radio"/>	Rear diff. oil cst.	60000		2n gear	20 / 49	Spring	silver xr		7,107 7,243 7,38	4,818 4,92 5,023
										4,588 4,686 4,783	

