



		Tires		Clutch settings		Front shocks		Engine								
Date/Track	Hokusei Circuit	Front shore	left Matrix 35/(Handout)	right Matrix 35/(Handout)	Shoe/Bell	Std. / Std.	Piston	φ1.3x1	Type	O.S. Speed T1201						
Driver	Takaaki Shimo	Rear shore	left Matrix 37/(Handout)	right Matrix 37/(Handout)	Bell clearance (mm)	0.5	Oil	#600	Plug/Fuel	Plug RP6 / Fuel Nitrox						
Temp. °C.	air / track	Front φ	left 63	right 63	Spring/adj. Nut(mm)	Std. / 0.2	Spring	Black	Pipe/Manifold	Pipe T-1070 / Manifold						
		Rear φ	left 65	right 65	Bell axial play (mm)	0.1			Rear shocks							
Track layout/traction	technical <input type="radio"/> low <input type="radio"/>	Differential			Gearing		Piston	φ1.1x2	Gear ratio chart							
	mixed <input checked="" type="radio"/> medium <input checked="" type="radio"/>	Front diff. oil cst.	#1,000,000		1st gear	15 / 54	Oil	#600	Spur Pinion	1st	2nd					
	fast <input type="radio"/> high <input type="radio"/>	Rear diff. oil cst.	#50,000		2n gear	20 / 48	Spring	Black	14	52	53	54	47	48	49	
									15	7,614	7,761	7,907				
										19				5,071	5,179	5,278
										20				4,818	4,92	5,023
										21				4,588	4,686	4,783

