

DRIVER	Kit Std. Setup EU Carpet Carbon		
DATE			
TRACK	Carpet <input type="radio"/> Asphalt <input checked="" type="radio"/>		
TRACTION	<input type="radio"/> LOW <input checked="" type="radio"/> MEDIUM <input type="radio"/> HIGH		
LAYOUT	<input checked="" type="radio"/> SLOW <input type="radio"/> MIXED <input type="radio"/> FAST		
TEMP °C	AIR	TRACK	
ELECTRONICS			
ESC	ESC SET	MOTOR	
SERVO	RECEIVER	BATTERY	
TIRES			
BRAND	Volante		
TYPE	28		
ADDITIVE	MR33V4		
WARMER °C	FRONT	REAR	
TIME(min)	FRONT	10	REAR 10
SHOCK ABSORBERS			
PISTON	FRONT	Kit	REAR Kit
SHOCK CASE	Kit		Kit
OIL	400		400
SPRING	6.5		6.25
ANTI ROLL BAR FRONT/REAR			
<input type="radio"/> 1,0 <input checked="" type="radio"/> 1,1 <input type="radio"/> 1,2			
<input type="radio"/> 1,0 <input checked="" type="radio"/> 1,1 <input type="radio"/> 1,2			
REAR DIFFERENTIAL			
DIFF OIL CST (1,6g oil qty.)	6000		
GEAR RATIO <small>(T)Spur/(T)Pinion*1,9=Ratio</small>			
PINION		SPUR	
AERODYNAMIC SETTINGS			
BODY TYPE	Twister		
WING TYPE	Twister		
WING POS	(mm)	neutral	
BODY POSITION (see picture below)	(mm) \leftrightarrow horizontal	52.5	
FRONT BODY HEIGHT & POSITION	REAR BODY POST A2407C	<input checked="" type="radio"/> REAR BODY POST A2416B	<input type="radio"/>
(mm) vertical \updownarrow	47	(mm)	48

FRONT

STEERING LIMITER
 A2304 (5mm)
 A2305 (5.5mm)
 A2306 (6mm)

STEERING ANGLE IN°
 ap.25

STEERING ANGLE OUT°
 16

A2421 USED
 YES
 NO

A2421 SHIM(mm)
 0

UPPER ARM POS. FR(mm)
 1.5

SHOCK POS (mm)
 3

UPPERARM POS. (CASTER)
 REAR/5° FRONT/4°

SHIM UPRIGHT T(mm)
 2

CAMBER/°
 2

TOE OUT/°
 1.25

FF(mm)
 1.5

STEERING ROD POS (mm)
 2

SHIM UPRIGHT L (mm)
 0.5

OFFSET (mm)
 4

LOWER ARM POS. FR(mm)
 1

SHIM UPRIGHT L (mm)
 0.5

RIDE HEIGHT(mm)
 5.1

DOWNSTOP(mm)
 6

REAR

ACKERMANN SHIM (mm)
 1

SHIM S HORN (mm)
 6

TYPE SERVO HORN

A2529 POSITION
 INSIDE
 OUTSIDE

LENGTH S HORN (mm)
 16.5

A2530 POSITION
 INSIDE
 OUTSIDE

REAR TOE ROD POS
 FRONT REAR

UPPERARM POS. (CASTER)
 FRONT/-4° REAR/-3°

UPPER ARM POS. RF(mm)
 1

SHOCK POS (mm)
 4

SHIM UPRIGHT T (mm)
 2

CAMBER/°
 2

TOE IN/°
 2.75

RR(mm)
 1

TOE ROD POS (mm)
 1.5

SHIM UPRIGHT L (mm)
 1.5

OFFSET (mm)
 4.5

LOWER ARM POS. RF(mm)
 1

RR(mm)
 1

RIDE HEIGHT(mm)
 5.3

DOWNSTOP(mm)
 4

BATTERY POSITION FRONT REAR

A2422(10g)
 A2422(10g)
 H2412 (18g)
 A2422(10g)

CHASSIS TYPE
 A2414

MM SCREW
 YES A2419
 NO

FRONT/REAR WEIGHT DISTRIBUTION HOLE# 1 2 3 4 5
 3-4

OPTIONAL WEIGHT
 A2422(10g)
 A2424
 A2425
 A2705
 A2706

WEIGHT(g)

BELT TENSION

FRONT POS.
 2

REAR POS.
 2

A2419 SCREW

1pc. UPPERDECK TYPE
 Kit

2pc. UPPERDECK TYPE

UPPERDECK SCREW
 A2158

REMARKS
 -ETS body height rule