



Name : _____
 Date : _____
 Track : _____

Track	Size:	Open	Med.	Tight
Conditions	Traction:	High	Med.	Low
	Surface:	Smooth	Bumpy	

Front suspension

Track width 199 mm
 Ride height 4 mm
 Camber angle -1 °
 Caster angle 2 mm
 Toe angle 0° ~ out 1 °
 Rebound stop +4 mm
 Bump stop
 ● None Use _____ mm

Front shocks

Piston Stock
 Oil # 600
 Spring Stock
 Tension _____ mm

Shock position

Front diff. Oil # 5000

Rear suspension

Track width 199 mm
 Ride height 5 mm
 Camber angle -1 °
 Toe angle in 1 °
 Rebound stop +8 mm
 Bump stop
 ● None Use _____ mm

Upper arm position

Anti-roll bar
 ● None Use _____ mm

Rear shocks

Piston Stock
 Oil # 600
 Spring Stock
 Tension _____ mm

Shock position

Rear diff. Oil # 5000

Engine

Type _____ Fuel _____
 Gasket _____ mm Muffler _____
 Plug _____

Clutch

● 3 P Clutch shoes ● Black
 White
 Spring Stock
 Other Clutch shoes _____
 Spring _____
 Clutch bell clearance _____ mm
 Clutch spring adj. nut _____ mm

Gear ratio 1st 16 / 47
 2nd 19 / 43

Brake pad ● Black Yellow

Tires & Wheels

Front Tire _____ Rear Tire _____
 Insert _____ Insert _____
 Wheel _____ Wheel _____

Body & Wing

Body _____ Wing _____

Result

Race time / Lap _____
 Best lap (1Lap) _____

Comments

.....

